

Technical Data Sheet

DOWSILTM 30-424 Additive

FEATURES & BENEFITS

- White silicone fine powder
- Contain methacryloxy group
- Light diffusion effect
- Similar diffusion effect compared to TREFIL E-606 at lower loading
- Hot spot suppression at lower loading compared to silicone benchmark
- Homogeneous dispersion throughout the complete light spectrum

COMPOSITION

Silicone Elastomer Powder

APPLICATIONS

- Additive for polystyrene
 - o Light diffuser for backlight module of LCD displayer
- Additive for polycarbonate
 - o Light diffuser for plastic cover of LED Lighting

TYPICAL PROPERTIES

Specification Writers: These values are not intended for use in preparing specifications.

Property	Unit	Result	
Appearance		White powder	
Average particle size	μm	2	
Particle size distribution	μm	1 - 3	
Bulk density	g/ml	0.2	

DESCRIPTION

DOWSILTM 30-424 Additive is a crosslinked methacryloxy functional silicone elastomer powder. Methacryloxy group could provide good dispersion in plastic matrix.

DOWSIL 30-424 Additive can provide good optical performance balance of transmittance, haze as well as diffusion effect. This powder could be used for light diffusion effect for LED lighting as well as for diffusion plate in backlight module of LCD displayer application.

HOW TO USE

When used as polycarbonate additive DOWSIL 30-424 Additive can be applied into twin screw extruder compounding process by pre-blending with the resin pellets or resin powder. Making master batch firstly for DOWSIL 30-424 Powder and then extruding it with resin could be another processing route with better dispersion effect.

Generally the loading of this powder

is approximately 0.1~1% to provide light diffusing effect in final polycarbonate matrix. The optimum level of loading should be determined by actual testing and application conditions.

HANDLING PRECAUTIONS PRODUCT SAFETY INFORMATION REQUIRED FOR SAFE USE IS NOT INCLUDED IN THIS DOCUMENT. BEFORE HANDLING, READ PRODUCT AND SAFETY DATA SHEETS AND CONTAINER LABELS FOR SAFE USE, PHYSICAL AND HEALTH HAZARD INFORMATION. THE SAFETY DATA SHEET IS AVAILABLE ON THE DOW WEBSITE AT WWW.CONSUMER.DOW.COM, OR FROM YOUR DOW SALES APPLICATION ENGINEER, OR DISTRIBUTOR, OR BY CALLING DOW CUSTOMER

SERVICE.

LIGHT DIFFUSING PERFORMANCES AT 0.5% LOADING ON 1.5MM THICKNESS PLATE

Property	Unit	Result	
Total transmittance	%	59	
Haze value	%	90	
Diffusion factor at 600nm (D50)		55	

TYPICAL MASTERBATCH FORMULATION (MB-5-E-POWDER)

Product	Dosage (in wt%)	
Lexan141R	94.3	
30-424 additive	5	
Irgafos 168	0.5	
Irganox 1010	0.2	

TYPICAL FORMULATION USING MASTERBATCH

Product	Dosage (in wt%)	
Lexan141R	89.3	
MB-5-E-powder	10	
Irgafos 168	0.5	
Irganox 1010	0.2	

USABLE LIFE AND STORAGE

When stored at or below 25°C in the original unopened containers, this product has a usable life of 27 months from the date of production.

PACKAGING INFORMATION

This product is available in 10kg/bag.

LIMITATIONS

This product is neither tested nor represented as suitable for medical or pharmaceutical uses.

HEALTH AND ENVIRONMENTAL INFORMATION

To support customers in their product safety needs, Dow has an extensive Product Stewardship organization and a team of product safety and regulatory compliance specialists available in each area.

For further information, please see our website, www.consumer.dow.com or consult your local Dow representative.

LIMITED WARRANTY INFORMATION – PLEASE READ CAREFULLY

The information contained herein is offered in good faith and is believed to be accurate. However, because conditions and methods of use of our products are beyond our control, this information should not be used in substitution for customer's tests to ensure that our products are safe, effective, and fully satisfactory for the intended end use. Suggestions of use shall not be taken as inducements to infringe any patent.

Dow's sole warranty is that our products will meet the sales specifications in effect at the time of shipment.

Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.

TO THE FULLEST EXTENT PERMITTED BY APPLICABLE LAW, DOW SPECIFICALLY DISCLAIMS ANY OTHER EXPRESS OR IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY.

DOW DISCLAIMS LIABILITY FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES. www.consumer.dow.com

