

SABIC[™] POE C5070 D

Polyolefin Elastomer

PRODUCT DESCRIPTION:

SABIC™ POE C5070 D is an ethylene octene copolymer produced by solution polymerization using metallocene catalyst. This product is available as free flowing pellets.

CHARACTERISTICS:

SABIC™ POE C5070 D is designed as a low density and high performance copolymer modifier to provide superior impact properties and flow characteristics.

TYPICAL APPLICATIONS:

- Impact modification
- Thermoplastic olefins
- Footwear
- · Wire and cable

TYPICAL DATA:

| PROPERTIES | Unit | Value (1) | Test Method |
|--|-----------|-----------|-------------|
| Physical | | | |
| Density | g/cm3 | 0.868 | ASTM-D 1505 |
| Melt Index (190°C/2.16 kg) | g/10 min. | 5.0 | ASTM-D 1238 |
| Mooney viscosity (ML 1+4, 121° C) | MU | 8 | ASTM-D 1646 |
| Hardness (2) | | | |
| Durometer Hardness, Shore A (1 second) | | 63 | ASTM-D 2240 |
| Durometer Hardness, Shore D (1 second) | | 16 | ASTM-D 2240 |
| Mechanical (2) | | | |
| Tensile Strength at break | MPa | 6 | ASTM-D 638 |
| Elongation | % | 1100 | ASTM-D 638 |
| 100% Modulus | MPa | 2.3 | ASTM-D 638 |
| Flexural Modulus- 1% Secant | MPa | 10.8 | ASTM-D 790 |
| Tear Strength, type C | kN/m | 35.3 | ASTM-D 624 |
| Thermal Properties | | | |
| Peak melting temperature | °C | 62 | |

DISCLAIMER: Products referred to in this document are sold subject to SABIC's Standard Terms and Conditions of Sale (the "Terms") which are available upon request. The information contained herein is supported by research and is believed to be reliable as of the date compiled and representative of production but no guarantee, representation or warranty, express or implied, is made or intended as to the correctness, sufficiency, suitability, merchantability or fitness for a particular purpose of any such information or the products to which it relates. Users are solely responsible for making their own determination as to the suitability of any product for their intended use and that such use is in compliance with applicable laws and standards. Nothing in this document is intended or should be construed to grant a license or immunity under any SABIC or third party intellectual property rights. Save and as expressly set out in the Terms, SABIC shall in no event be liable for any loss, damage or injury howsoever arising from the use of information or the products referred to herein.

© 2012 Saudi Basic Industries Corporation. SABIC and the SABIC emblem are trademarks of Saudi Basic Industries Corporation or its affiliates.



(1) Typical values; not to be construed as specification limits.

(2) All physical properties were measured from specimens cut from compression molded. These typical values depend on manufacturing conditions. Therefore, customers should confirm the product performance by using their own tests.

PACKING & STORAGE:

The product is available in 1.25 tons pallets containing 50 bags of approximately 25 kg each. SABIC will not extend its warranty when storage conditions are inadequate which may lead to quality deterioration such as color change that could result in inadequate product performance. The storage area should be at ambient temperature (recommended not to exceed 30 °C) in dry conditions; flow ability of the pellets can be negatively influenced by pressure or high temperature; exposure to light has to be avoided. The product has shelf life time of 24 months from the date of production.

CONTACT US:

Saudi Basic Industries Corporation P.O. Box 5101 Riyadh 11422 Kingdom of Saudi Arabia Tel: 966 11 2258000

Fax: 966 11 2259000

Technical Marketing

Tel: 966 11 2258630 Fax: 966 11 2258730 Email: fp_pcsbu@sabic.com Website: www.sabic.com

Application Development (SPADC)

Tel: 966 11 2501948 Email: fp_pcsbu@sabic.com Website: www.sabic.com

Note: The information and data contained herein are believed to be correct and given in good faith, but because of the many particular factors which are outside our knowledge and control and affect the use of the product, no warranty is given or to be implied with respect to such information, nor do we offer any immunity against infringement.

DISCLAIMER: Products referred to in this document are sold subject to SABIC's Standard Terms and Conditions of Sale (the "Terms") which are available upon request. The information contained herein is supported by research and is believed to be reliable as of the date compiled and representative of production but no guarantee, representation or warranty, express or implied, is made or intended as to the correctness, sufficiency, suitability, merchantability or fitness for a particular purpose of any such information or the products to which it relates. Users are solely responsible for making their own determination as to the suitability of any product for their intended use and that such use is in compliance with applicable laws and standards. Nothing in this document is intended or should be construed to grant a license or immunity under any SABIC or third party intellectual property rights. Save and as expressly set out in the Terms, SABIC shall in no event be liable for any loss, damage or injury howsoever arising from the use of information or the products referred to herein.

© 2012 Saudi Basic Industries Corporation. SABIC and the SABIC emblem are trademarks of Saudi Basic Industries Corporation or its affiliates.