

双硬脂酸铝(Aluminum Ethyl Stearate)**产品性质**

本品为白色粉末,不溶于水,微溶于乙醇,溶于石油醚、碱水溶液等,本品无毒。

产品指标

质量指标 符合 HG2338-92(优等品)

项目		指标
铝含量	%	4.0~5.2
加热减量(105±3℃)%	≤	1.5
筛余物(通过0.075mm筛)%	≥	97.0
游离酸(以硬脂酸计)%	≤	8.0
熔点℃		165~175

产品用途

本品广泛用作聚氯乙烯稳定剂,金属防锈剂原料,建筑材料防水剂,涂料和油墨增稠剂。

包装及储存

- 本品宜在通风、干燥、阴凉处储存,注意防潮、避光、防热。
- 本品包装为塑料编织袋内衬薄膜袋,净重10kg。

Aluminum Ethyl Stearate**Product character**

Fine white powder, insoluble in water, slightly soluble in ethanol, soluble in petroleum ether, alkali solution. Non-toxic

Specification

Items		Specification
Aluminum Content	%	4.0~5.2
Heating loss (105 ±3℃)%	≤	1.5
Fineness (thr. 0.075mm screen), %	≥	97.0
Free Fatty Acid(As Stearic acid)%	≤	8.0
Melting Point °C		165~175

Applications

They are widely used as lubricants, slipping agents, heat-stabilizers, mouldreleasing agents and accelerants in plastic, machinery engineering, rubber, paints and inks industry etc.

Packing and Storage

In net 10 kg polywoven bags. Keep it in airtight containers and dry, cool and dark place. Damp-proof, sun protection and far from fire.